


FR 14P - miniature relay



Miniaturised PCB-relay with three change-over contacts for industrial electronics.

order numbers

PCB version FR14P.VDC/VAC

contact specifications

(see data sheet for curves)

contact material	AgCuNi
contact type	single contact
nominal switching capacity	250 VAC 4 A AC1 1000 VA
electric life expectancy	app. 200'000 operations 250 VAC 4A AC1 (360 operations/h)
inrush current max.	15A for 200 ms
switching current range	50 mA to 4A
switching power range	0,3VA to 1000VA

options

contact material AgCuNi
 AgCuNi+Au10µm
(see data sheet for contacts)

general data


mechanic life expectancy	> 50 x 10 ⁶ operations
switching frequency mechanical	20 Hz
pull-in time	8 ms at DC / 3-9 ms at AC
release time	2,5 ms at DC / 4-12 ms at AC
bounce time normally open contact	3 ms at DC / 1-8 ms at AC
bounce time break contact	8 ms at DC / 3-16 ms at AC
shock resistance	AK: >10 g
test voltage, coil/contact	2'000 V _{eff}
test voltage, open contact	1'000 V _{eff}
insulation resistance	250 MΩ
weight	38 g
installation situation	any
ambient temperature	max. +60 °C

accessories


PCB socket ZB 107
metal clamp ZFR004

tests, instructions

certificates UL, CSA, VDE




FR 14P




circuit diagram

FR 14P



drilling plan (view on solder side)

dimensions



coil specifications

standard coils for direct current
(other voltages on enquiry)

rated voltage VDC	pull-in voltage at 20 °C	reset voltage at 20 °C	nominal current mA	resistance Ohm at 20 °C	tolerance %
12	10,2	≥ 0,6	109	110	+/-10
24	20,4	≥ 1,2	52,1	460	+/-10
36	30,6	≥ 1,8	36,0	1'000	+/-10
48	40,8	≥ 2,4	28,2	1'700	+/-10
110	93,5	≥ 5,5	11,5	9'500	+/-15


standard coils for alternated current
(other voltages on enquiry)

VAC	pull-in voltage at 20 °C	reset voltage at 20 °C	nominal current mA	resistance Ohm at 20 °C	tolerance %
12	10,2	≥ 0,6	148	30	+/-10
24	20,4	≥ 1,2	68,5	130	+/-10
36	30,6	≥ 1,8	46,7	300	+/-10
48	40,8	≥ 2,4	35,5	540	+/-10
110	93,5	≥ 5,5	16,4	2'900	+/-15
220	187	≥ 11,0	6,1	14'500	+/-15
230	195	≥ 11,5	5,8	15'000	+/-15



FR - contact specifications


AgCuNi 4A



- resistive load

data valid for relay	FR 11 FR 14
contact material	AgCuNi (AgCu 1,88 Ni0,12)
contact type	single contact
nominal switching capacity	250VAC 4A AC1 1000VA
electric life expectancy	app. 200'000 operations 250 VAC 4A AC1 (360 operations/h)
inrush current max.	15A for 200 ms
switching current range	50mA to 4A
switching power range	0,3VA to 1000VA

AgCuNi+Au 10µm



- resistive load

data valid for relay	FR 11 FR 14
contact material	AgCuNi+Au 10µm
contact type	single contact
nominal switching capacity	250VAC 2A AC1 500VA
electric life expectancy	app. 100'000 operations 250 VAC 2A AC1 (360 operations/h)
inrush current max.	6A for 200 ms
switching current range	10mA to 2A
switching power range	0,06VA to 500VA

